


MATERIAL:
Housing: PBT 94V-0 COLOR:BLUE
Contact: copper alloy (T=0.25mm)
Shell: C5191

PLATING:
Contact: Au Plated on contact area
Tin Plated on solder area
Nickel underplating over all
Shell: Nickel Plated
operating Temperature:-55° to+85°

12=半金雾锡1U"			
13=半金雾锡3U"			
14=半金雾锡5U"			
15=半金雾锡15U"			
16=半金雾锡30U"			
00="PT"蓝磷铜外壳镀镍	R=ROHS2.0标准		
	W=无卤+ROHS2.0		
	R=REACH标准		
			R=盐雾24H
			(=盐雾48H

Pin Number	Signal Name	 东莞市兴科杰鑫电子有限公司 Dong Guan XingKeJieXin Electronics Co.,Ltd									
1	VBUS	UNLESS OTHERWISE SPECIFIED TOLERANCES METRIC X. +/- .X +/- .XX +/- FRACTIONS ANGLES +/- 2.00"		APPROVAL		日期	品名规格	Conn B AF 180° DIP (有卷边直脚, 脚长3.0封胶款带护套)			
2	D-			制图							
3	D+			审核							
4	GND			核准			料号	SEE TABLE			
5	SSRX-			文件位置							
6	SSRX+	ANGLE OF PROJECTION 		字张	工程图号:			版本.			
7	GND			A4					DWG-USBAF-253		
8	SSTX-			DIMENSIONS (METRIC) (MM)		比例	1 : 1	状态码	C	页数	1 OF 1
9	SSTX+	Shell Shield									