

REV.	ECN NO.	DESCRIPTION	DRAW	CHECK	APPD.	DATE
A1	ECN221130001	增加包装规格	Dream	BENDEE	BENDEE	2022.12.02
A2	ECN240326001	1. 增加外壳脚脚 2. 增加紫色规格 3. 新增包规	Simon	Linson	Rambo	2024.03.26


SPECIFICATIONS:

Contact current Rating:
1.8 Amperes for pin1&pin4.
0.25 Amperes other contacts
Dielectric Withstanding Voltage:AC 100V(RMS)
Insulation resistance:100Megohms Minimum.
Contact Resistance:
30mΩ Max for pin1&pin4
50mΩ Max for other contacts
Mechanical Characteristics:
Mating Force:35 Newtoms.Maximum
Unmating Force:10 Newtoms.Mlimum.
8N Min After Durability

MATERIAL:

Housing: PBT+30%GF 94V-0
Contact: copper alloy(T=0.25mm)
Shell: Brass
operating Temperature:-55°to+85°

料号备注										B=PACK-T0124 A=PACK-T0299 T=PACK-T0033	A2
CU	3	F	399	S	XX	T	XX	XX	XX		
12=半金雾锡10"	13=半金雾锡30"	14=半金雾锡50"	15=半金雾锡150"	16=半金雾锡300"	02=PBT紫色(Violet 0) 后塞加锡 铜壳镀镍	01=PBT灰10C铜壳镀镍	00=PBT蓝铜壳镀镍	R=ROHS2.0标准 W=无卤+ROHS2.0	B=盐雾24H C=盐雾48H		

Pin Number		Signal Name		东莞市兴科杰鑫电子有限公司 Dong Guan XingKeJieXin Electronics Co.,Ltd											
1		VBUS			UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL		日期		品名规格	USB 3.0 AF 180° 焊线 A款 无卷边 (焊线脚偏移 后塞加厚款带定位柱 外壳铆脚)			
2		D-					制图 Simon		2024.03.26						
3		D+					审核								
4		GND					核准								
5		SSRX-			X. +/- 0.30 .X +/- 0.25 .XX +/- 0.20		FRACTIONS +/- ANGLES +/- 2.00°		ANGLE OF PROJECTION		料号	SEE TABLE			
6		SSRX+													
7		GND													
8		SSTX-			DIMENSIONS				字张 A4	工程图号: DWG-USBAF-461			版本. A2		
9		SSTX+													
Shell		Shield		(METRIC)		(MM)		比例		1 : 1		状态码 A		页数 1 OF 1	



东莞市兴科杰鑫电子有限公司
Dong Guan XingKeJieXin Electronics Co.,Ltd

