

HSF Compliant

REV.	ECN NO.	DESCRIPTION	DRAW	CHECK	APPD.	DATE
A0	—	新版发行	YIN	—	BENDEE	23-04-27
A1	ECN240301001	改善脱壳:扣孔加大	Yin	Linson	Rambo	24-03-01

Specifications:

- 1.0 Electrical performance:
- 1.1 Contact resistance: 30mΩ max
- 1.2 Dielectric withstanding voltage:AC 300V(rms).
- 1.3 Insulation resistance:100MΩ min.
- 1.4 Contact current rating:
2A for VCC And GND
- 1.5 Voltage: 12 Vdc (rms).
- 2.0 mechanical performance:
- 2.1 Mating force:45N Max
- 2.2 Unmating force:10N Min
- 2.3 Durability:1000 cycles.
- 3.0 Environmental performance:
- 3.1 Temperature range:
- 3.2 Operating temperature:+5°to+55°.
- 3.3 Storage temperature:-20°to+70°.
- 4.0 Material:
- 4.1 Housing:LCP Black,UL94V-0.
- 4.2 Insert Molding:LCP Black,UL94V-0.
- 4.3 Contact:C7025,T=0.25mm
- 5.0 Plating specification:
- 5.1 Contact: G/F Au plated on contact area;
Matte Tin plated 50u"min on solder area;
Nickel 50u"min underplating over all.
- 6."**" Shows FAI measurement point.

料号备注

T=PACK-T0288

CK	0	M	004	B	XX	X	XX	X	X
----	---	---	-----	---	----	---	----	---	---

12=半金雾锡1U"

15=半金雾锡15U"

16=半金雾锡30U"

00=LCP黑

R=ROHS2.0标准

B=盐雾24H



东莞市兴科杰鑫电子有限公司
Dong Guan XingKeJieXin Electronics Co.,Ltd

UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL	日期	品名规格	风扇线端插头夹板式	
X. +/-		制图	YIN	2024.03.01	SEE TABLE	
.X +/-		审核				
.XX +/-		核准				
FRACTIONS +/-		文件位置		料号	工程图号:	
ANGLES +/-		2.00'		字张	A4	
DIMENSIONS		ANGLE OF PROJECTION		比例	1 : 1	
(METRIC)	(MM)			状态码	A	
				页数	1 OF 1	