


- 1.0 Electrical Characteristics:
 - 1.1 Contact current Rating:
5 Amperes per pin
 - 1.2 Dielectric Withstanding Voltage:AC 500V(RMS)
 - 1.3 Insulation resistance:1000Megohms Minimum.
 - 1.4 Contact Resistance:
Initial:30mΩ Max for mated connector
final(after stress)50mΩMax
- 2.0 Material:
 - 2.1 Housing: Thermoplastic 94V-0
Colour:Black
 - 2.2 Contact: Copper alloy
- 3.0 PLATING:
Contac : Tin plated
Nickel underplating overall
- 4.0 Operating Temperature:-20°to+85°

04=2X2Pin	11=镀亮锡100U"	01=PA66黑色 00=PA66白色	R=ROHS2.0标准
-----------	-------------	------------------------	-------------

 东莞市兴科杰鑫电子有限公司 Dong Guan XingKeJieXin Electronics Co.,Ltd									
UNLESS OTHERWISE SPECIFIED TOLERANCES METRIC X. +/— 0.30 .X +/— 0.20 .XX +/— 0.10 FRACTIONS +/— ANGLES +/— 2.00° DIMENSIONS (METRIC) (MM)		APPROVAL		日期		品名 规格		ATX 3.0 PITCH POWER CONN	
		制图 Tomath		2024.09.19					
		审核 Linson		2024.09.19		料号		SEE TABLE	
		核准 Rambo		2024.09.19					
		文件位置		字张		工程图号：		版本.	
		ANGLE OF PROJECTION		A4		DWG-CA0F-001		A0	
				比例		1 : 1		状态码 A	
						页数		1 OF 1	