

SPECIFICATIONS:

- 1.0 Electrical Characteristics:
 - 1.1 Contact current Rating:
3 Amperes per pin
 - 1.2 Dielectric Withstanding Voltage:AC 500V(RMS)
 - 1.3 Insulation resistance:1000Megohms Minimum.
 - 1.4 Contact Resistance:
Initial:30mΩ Max for mated connector
final(after stress)50mΩMax
- 2.0 Material:
 - 2.1 Housing: Thermoplastic 94V-0
Colour:Blue/Yellow/Red/White/Black
 - 2.2 Contact: Copper alloy
- 3.0 PLATING:
Contac : Gold flash
Nickel underplating overall
- 4.0 Operating Temperature:-20°to+85°

01=1Pin		04=PA6T 蓝色	
S	17=镀全金 G/F	03=PA6T 黄色	
		02=PA6T 红色	
	11=镀全锡	01=PA6T 白色	W=RoHS2.0+HF
		00=PA6T 黑色	R=RoHS2.0标准
20=20Pin			B=盐雾24H


 东莞市兴科杰鑫电子有限公司
 Dong Guan XingKeJieXin Electronics Co.,Ltd

UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL		品名		排针 2.54 PITCH (单排)			
METRIC		日期		规格					
X. +/- 0.30		制图 Tomath 2024.09.19		料号		SEE TABLE			
.X +/- 0.20		审核 Linson 2024.09.19							
.XX +/- 0.10		核准 Rambo 2024.09.19							
FRACTIONS +/-		文件位置		字张		工程图号:			
ANGLES +/- 2.00°		ANGLE OF PROJECTION							
DIMENSIONS				A4		DWG-CEOM-004			
(METRIC)	(MM)			比例		1 : 1			
				状态码		A		页数 1 OF 1	