

REV.	ECN NO.	DESCRIPTION	DRAW	CHECK	APPD.	DATE
A0		新版发行	Erica	Linson	Rambo	

NOTES:

1.Material:

Housing:Thermoplastic UL 94V-0,Black

Terminal:Copper Alloy

2.Finish:Plating Gold

3.Specification

Current Rating: 8A Max./Pin

Voltage Rating: 30V Max.

Contact Resistance: 50m ohm Max.

Insulation Resistance: 1000M ohm Min.

Dielectric Voltage: 500V

Operating Temperature:-25°C ~ 85°C

料号备注

C3 0 F 001 M XX X XX X X

G1=全金G/F

G2=全金2u"

G3=全金5u"

G4=全金10u"

G5=全金15u"

G6=全金30u"

00=LCP 黑

01=PA6T 黑

R=ROHS2.0标准

W=无卤+ROHS2.0

B=盐雾24H



东莞市兴科杰鑫电子有限公司

Dong Guan XingKeJieXin Electronics Co.,Ltd

UNLESS OTHERWISE SPECIFIED TOLERANCES METRIC X. +/- 0.30 .X +/- 0.25 .XX +/- 0.20 FRACTIONS +/- ANGLES +/- 2.00°			APPROVAL		日期		品名 规格		电池座 3P Female PH2.0 90° SMT 有定位柱			
			制图 Erica						料号			
			审核 Linson									
			核准 Rambo									
			文件位置				料号		SEE TABLE			
ANGLE OF PROJECTION				字张		工程图号:			版本.			
				A4		DWG-BATTERY F-001			A0			
				比例		1 : 1			状态码			
						A			页数			
								1		OF 1		