

2		1				
REV.	ECN NO.	DESCRIPTION	DRAW	CHECK	APPD.	DATE
A0		新版发行	Erica	Linson	Rambo	

NOTES:

1.Material:

Housing:Thermoplastic UL 94V-0,Black
Terminal:Copper Alloy

2.Finish:Plating Gold

3.Specification

Current Rating: 1A Max./Pin

Voltage Rating: 30V Max.

Contact Resistance: 50m ohm Max.

Insulation Resistance: 1000M ohm Min.

Dielectric Voltage: 500V

Operating Temperature:-20°C ~ 80°C

料号备注

C3 0 M 002 D XX X XX X X

G1=全金G/F

G2=全金2u"

G3=全金5u"

G4=全金10u"

G5=全金15u"

G6=全金30u"

00=LCP 黑

01=PA6T 黑

R=ROHS2.0标准

W=无卤+ROHS2.0

B=盐雾24H



东莞市兴科杰鑫电子有限公司

Dong Guan XingKeJieXin Electronics Co.,Ltd

UNLESS OTHERWISE SPECIFIED TOLERANCES X. +/- METRIC 0.30 .X +/- 0.25 .XX +/- 0.20 FRACTIONS +/- ANGLES +/- 2.00° DIMENSIONS (METRIC) (MM)	APPROVAL		日期	品名	电池座 8P Male PH2.0 90° DIP
	制图	Erica		规格	
	审核	Linson		料号	SEE TABLE
	核准	Rambo		工程图号:	
	文件位置		ANGLED OF PROJECTION	字张	DWG-BATTERY M-002
				A4	版本
				比例	1 : 1
				状态码	A
				页数	1 OF 1